AISG Assembly




DB9M-AISG8F PVC6C Lm

HXAG00007 Rev:A0


ID:

DB9M TO AISG8F




^{*}The above picture is only for reference, we may change the appearance design in order to enhance performance without notification.

Product Description



DB9 Male		AISG Female
1	$\left \leftarrow\right $	1
1		6
3	$\left \leftarrow\right>$	3
5	$\langle \cdots \rangle$	5
4	\leftarrow	4
9	$] \longleftarrow \longrightarrow$	7
	1 / 3 5 4	1



Electrical Specifications

 Rated voltage
 300V AC

 Rated impulse withstand voltege
 500V

 Current rating
 5A at 50° C

 Insulation resistance
 $> 100M\Omega$

 Contact resistance
 $< 5m\Omega$

Environmental & Mechanical Specifications

Mechanical operation 500cycles

Insertion and withdrawal forces 40N

IP-degree IP68 at mating

Others Characteristics

 Temperature Range
 -40°C to +85°C

 Cable
 PVC

 Injection material
 PE

 Jacket O.D.
 7.8mm

Length 0.5m/1m/2m/3m/5m/10m/20m/30m/40m/50m/70m/100m

The facts and figures contained herein are carefully complied to the best of our knowledge, but they are intended for general informational purposes only.

Jiangsu Hengxin Technology Co.,Ltd